

# ADVENTURE LX



## ROTAX® ENGINE

**600 ACE**

|                              |                                     |
|------------------------------|-------------------------------------|
| <b>Engine details</b>        | Liquid-cooled, four-stroke D.O.H.C. |
| <b>Cylinders</b>             | 2                                   |
| <b>Displacement</b>          | 600 cc                              |
| <b>Bore</b>                  | 74 mm                               |
| <b>Stroke</b>                | 69.7 mm                             |
| <b>Maximum engine speed</b>  | 7250 RPM                            |
| <b>Carburation</b>           | EFI                                 |
| <b>Recommended fuel type</b> | Unleaded                            |
| <b>Minimum octane</b>        | 95                                  |
| <b>Fuel tank</b>             | 37 liters                           |

## COLOUR

Viper Red/Black

## DIMENSIONS

|                                |             |
|--------------------------------|-------------|
| <b>Vehicle overall length*</b> | 3060 mm     |
| <b>Vehicle overall width</b>   | 1280 mm     |
| <b>Vehicle overall height</b>  | 1470 mm     |
| <b>Ski stance</b>              | 1080 mm     |
| <b>Track nominal width</b>     | 381 mm      |
| <b>Track nominal length</b>    | 3487 mm     |
| <b>Track profile height</b>    | 34 mm Cobra |

## POWERTRAIN

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| <b>Drive clutch type</b>  | eDrive II                                                              |
| <b>Driven clutch type</b> | QRS                                                                    |
| <b>Brake system</b>       | Hydraulic brake with braided steel brake line, plastic master cylinder |

## SUSPENSION

|                         |                        |
|-------------------------|------------------------|
| <b>Front suspension</b> | LFS                    |
| <b>Front shock</b>      | HPG 36                 |
| <b>Rear suspension</b>  | PPS <sup>2</sup> -3500 |
| <b>Center shock</b>     | HPG 36                 |
| <b>Rear shock</b>       | HPG 36                 |

## FEATURES

|                              |                  |                                |                                 |
|------------------------------|------------------|--------------------------------|---------------------------------|
| <b>Frame</b>                 | Radien-X         | <b>Heated grips</b>            | Standard                        |
| <b>Skis</b>                  | Blade DS+        | <b>Gauge</b>                   | 4.5-in. digital display         |
| <b>Seating</b>               | 2-up             | <b>Windshield</b>              | Extra high with side deflectors |
| <b>Handlebar</b>             | Steel with hooks | <b>Visor Plug front / rear</b> | Front                           |
| <b>Riser block height</b>    | 120 mm           | <b>12V power outlet</b>        | Yes, in front compartment       |
| <b>Starter</b>               | Electric         | <b>Air radiator with fan</b>   | Yes                             |
| <b>Reverse</b>               | Mechanical       | <b>LinQ attachment</b>         | 1 pair                          |
| <b>Heated throttle lever</b> | Standard         |                                |                                 |

\* Vehicle overall length without snowflap.