

HIGHLIGHTS

- Rotax® V-Twin engine
- Arched double A-arm front suspension with front sway bar
- Torsional Trailing arm Independent (TTI) rear suspension
- Front and rear FOX† 1.5 PODIUM† shocks
- Intelligent Throttle Control (iTC™) with riding modes
- 30-in. (76.6 cm) ITP Cryptid† tires
- 14-in. (35.6 cm) cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-4Lok front differential
- Relocated radiator
- 3,500-lb (1,588 kg) winch
- Heavy-duty front and rear bumpers
- Mud-riding footrests
- 59-in. (149.9 cm) wheelbase
- Multifunction digital gauge
- X-package coloration, graphics and seat cover
- Mudguards



 Liquid Titanium & Magma Red

ENGINE

Type	68 k W (91 hp), Rotax® 976 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar
Front Shocks	FOX† 1.5 PODIUM†
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX† 1.5 PODIUM†

TIRES / WHEELS

Front Tires	ITP Cryptid 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1014 lb (460 kg)
L x W x H	97 x 50 x 51.5 in. (246 x 127 x 131 cm)
Wheelbase	59 in. (149.9 cm)
Ground Clearance	13 in. (33 cm)
Seat Height	36.75 in. (93.3 cm)
Rack Capacity	Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

Gauge	7.6-in wide digital display: Speedometer, tachometer, odometer, trips & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge, clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
Seat	Standard
Protection	Heavy-duty front & rear bumpers Mud-riding footrests Mudguards

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------