

MY24 COMMANDER MAX XT 1000R



■ Triple Black

HIGHLIGHTS

- 64 in. (162.6 cm) wide with Arched A-arm
- 7.6 in. (19.3 cm) digital display with keypad
- Can-Am LED signature
- 28 in. (71.1 cm) XPS Trail King tires
- 14 in. (35.6 cm) cast-aluminum wheels
- XT front bumper
- 4,500-lb (2,041 kg) winch
- Full roof

ENGINE

Type	75 kW (100 hp), Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 15 in. (38.1 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with sway bar / 15 in. (38.1 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS

Front Tires / Rear Tires	XPS Trail King 28 x 9 / 11 x 14 in. (71.1 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front / Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers
--------------	---

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1,930 lb (875.4 kg)
Chassis / Cage	Profiled cage. ROPS approved
L x W x H	160.4 x 64 x 76.2 in (407.4 x 162.6 x 193.5 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	13 in (33 cm)
Cargo Box Dimension	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC outlet (10-A)
Ignition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	Front lighting output 110 W LED signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Full roof Premium half doors Full skid plate Mudguards XT front bumper
Hitch Type	2-in hitch receiver

WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.