

MY24 MAVERICK X MR TURBO RR



 Hyper Silver & Legion Red

HIGHLIGHTS

- Smart-Lok™ front differential
- FOX† 2.5 PODIUM QS3 Piggyback shocks
- Snorkeled engine air intake and CVT
- Belt monitoring system
- 850 W Magneto
- 7.6 in. (19.3 cm) digital display with keypad
- X-package graphics/seats
- Can-Am LED signature
- 14 in. (35.6 cm) cast-aluminum beadlock wheels
- 30 in. (76.2 cm) ITP Cryptid tires
- Front bumper
- Half-doors
- Front tow hook
- 4,500-lb (2,041 kg) winch with synthetic rope
- HMWPE full skid plate

DIMENSIONS / CAPACITIES

Estimated Dry Weight **	1,758 lb (797.4 kg)
Chassis / Cage	Dual-phase 980 steel
L x W x H	132.3 x 74.2 x 68 in. (336 x 188.5 x 172.7 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC Outlet (10-A)
Magneto	850 W
Ignition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights LED signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Protection	Front bumper Half-doors Front and rear tow hooks HMWPE full skid plate

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------

*149kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRRM certification.

ENGINE

Type	149 kW (200 hp*), Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler, high-performance air filter and strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 22 in. (55.9 cm) travel / Trophy truck inspired arms
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links / 22 in. (55.9 cm) travel
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment and bottom-out control

TIRES / WHEELS

Front & Rear Tires	ITP Cryptid 30 x 9 / 11 x 14 in. (76.2 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum beadlock

BRAKES

Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. **Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.